

SLED FL 120B LED Flood Lighting



PECIFACATION

LED Flood Lighting

| | |
|-------------------|--------------------|
| LED type | COB |
| Power (W) | 120W |
| Dimension | 450*200*200mm |
| Color index (CRI) | ≥75Ra |
| Efficacy (lm/W) | 8500lm/W |
| Decline | <3% within 3000Hrs |
| Life time (Hrs) | ≥50,000H |
| Humidity | 5 to 95% R.H. |
| Work temperature | -20~+55°C |
| Power factor (PF) | ≥0.95 |
| Warranty | 3 years |
| Certificate | UL CE FCC RoHS SAA |
| Dimension (mm) | 425*325*190 |

Main Features of Led Flood Lighting

1. high heat conducting efficiency, low lumens depreciation, high light purity, and no double image
2. IP65 standard, free from water, dust and corrosion
3. Breadth working voltage, and constant flow and pressure
4. Environmental protection, no pollution of lead and Hg
5. The decorative effect is wonderful, the surface adopted special process

Illuminant parameters of Flood Lighting

Input Voltage: AC 85V - 265V; LED type: High power led
 Frequency (Hz):47 to 63Hz, Color index (CRI): ≥ 80Ra
 Power efficiency: ≥ 85 % , Power factor (PF):≥ 0.95
 IP65, Color range: 2800 - 7500K

Appearance parameters of Led Flood Lighting

Lamp Body Material: Aluminum
 Color of lamp shell: Gray

