

LED Roof Lighting




Normal Mode



SLED GS00101

110-240V 50/60Hz	SMD 3528	602 LEDs	38 W	3600 lm	IP 65		
----------------------------	-----------------	-----------------	-------------	----------------	--------------	--	--

Environmental Temperature: -20°C~60°C
 Environmental Humidity: 0%~95%
 Material: PC
 Driver: Included




Lux-Distance Curve

Height	Illuminance	Beam Angle: 114.80 Deg	Diameter
1m	1265.16 lx		313.39 cm
2m	301.81 lx		626.77 cm
3m	133.81 lx		940.16 cm
4m	78.32 lx		1253.54 cm
5m	48.21 lx		1566.92 cm
6m	33.48 lx		1880.30 cm
7m	24.30 lx		2193.68 cm
8m	18.38 lx		2507.06 cm
9m	14.88 lx		2820.44 cm
10m	12.00 lx		3133.82 cm
11m	9.88 lx		3447.20 cm
12m	8.37 lx		3760.58 cm
13m	7.38 lx		4073.96 cm
14m	6.75 lx		4387.34 cm
15m	6.32 lx		4700.72 cm
16m	6.05 lx		5014.10 cm

SLED GS00104

110-240V 50/60Hz	SMD 3528	301 LEDs	19 W	1900 lm	IP 65		
----------------------------	-----------------	-----------------	-------------	----------------	--------------	--	--

Environmental Temperature: -20°C~60°C
 Environmental Humidity: 0%~95%
 Material: PC
 Driver: Included



Lux-Distance Curve

Height	Illuminance	Beam Angle: 112.30 Deg	Diameter
1m	646.88 lx		286.18 cm
2m	161.74 lx		572.36 cm
3m	71.38 lx		858.54 cm
4m	40.43 lx		1144.72 cm
5m	28.80 lx		1430.90 cm
6m	17.87 lx		1717.08 cm
7m	13.20 lx		2003.26 cm
8m	10.11 lx		2289.44 cm
9m	7.39 lx		2575.62 cm
10m	5.47 lx		2861.80 cm
11m	4.38 lx		3147.98 cm
12m	3.69 lx		3434.16 cm
13m	3.25 lx		3720.34 cm
14m	2.93 lx		4006.52 cm
15m	2.68 lx		4292.70 cm

