

## SLED FL 100B LED Flood Lighting



### PECIFACATION

#### LED Flood Lighting

LED type	COB
Power (W)	100W
Dimension	360*287*120mm
Color index (CRI)	≥75Ra
Efficacy (lm/W)	8500lm/W
Decline	<3% within 3000Hrs
Life time (Hrs)	≥50,000H
Humidity	5 to 95% R.H.
Work temperature	-20~+55°C
Power factor (PF)	≥0.95
Warranty	3 years
Certificate	UL CE FCC RoHS SAA
Dimension (mm)	370*290*85

### Main Features of Led Flood Lighting

1. high heat conducting efficiency, low lumens depreciation, high light purity, and no double image
2. IP65 standard, free from water, dust and corrosion
3. Breadth working voltage, and constant flow and pressure
4. Environmental protection, no pollution of lead and Hg
5. The decorative effect is wonderful, the surface adopted special process

### Illuminant parameters of Flood Lighting

Input Voltage: AC 85V - 265V; LED type: High power led  
 Frequency (Hz):47 to 63Hz, Color index (CRI): ≥ 80Ra  
 Power efficiency: ≥ 85 % , Power factor (PF):≥ 0.95  
 IP65, Color range: 2800 - 7500K

### Appearance parameters of Led Flood Lighting

Lamp Body Material: Aluminum  
 Color of lamp shell: Gray

