

**PECIFACATION**

LED Flood Lighting

LED type	COB
Power (W)	200W
Dimension	525*325*190mm
Color index (CRI)	≥75Ra
Efficacy (lm/W)	8500lm/W
Decline	<3% within 3000Hrs
Life time (Hrs)	≥50,000H
Humidity	5 to 95% R.H.
Work temperature	-20~+55°C
Power factor (PF)	≥0.95
Warranty	3 years
Certificate	UL CE FCC RoHS SAA
Materials	Aluminium alloy die casting



**Main Features of Led Flood Lighting**

1. high heat conducting efficiency, low lumens depreciation, high light purity, and no double image
2. IP65 standard, free from water, dust and corrosion
3. Breadth working voltage, and constant flow and pressure
4. Environmental protection, no pollution of lead and Hg
5. The decorative effect is wonderful, the surface adopted special process

**Illuminant parameters of Flood Lighting**

Input Voltage: AC 85V - 265V; LED type: High power led  
 Frequency (Hz):47 to 63Hz, Color index (CRI): ≥ 80Ra  
 Power efficiency: ≥ 85 % , Power factor (PF):≥ 0.95  
 IP65, Color range: 2800 - 7500K

**Appearance parameters of Led Flood Lighting**

Lamp Body Material: Aluminum  
 Color of lamp shell: Gray

