### **SLED FL 30B LED Flood Lighting**





### **PECIFACATION**

## **LED Flood Lighting**

LED type	COB
Power (W)	30W
IP grade	IP65
Input voltage(V)	85~265V AC
Color index (CRI)	≥80
Efficiency	≥85%
Frequency (Hz)	47 to 63Hz
Decline	<3% within 3000Hrs
Life time (Hrs)	≥35,000H
Humidity	5 to 95% R.H.
Work temperature	-20 <b>~</b> +65°C
Stock temperature	-40 <b>~</b> +85°C
Dimension (mm)	225*185*120

# Main Features of Led Flood Lighting

- 1. high heat conducting efficiency, low lumens depreciation, high light purity, and no double image
- 2. IP65 standard, free from water, dust and corrosion3. Breadth working voltage, and constant flow and pressure
- 4. Environmental protection, no pollution of lead and Hg
- 5. The decorative effect is wonderful, the surface adopted special process

### Illuminant parameters of Flood Lighting

Input Voltage: AC 85V - 265V; LED type: High power led Frequency (Hz):47 to 63Hz, Color index (CRI): ≥ 80Ra Power efficiency: ≥ 85 %, Power factor (PF):≥ 0.95

IP65, Color range: 2800 - 7500K

## **Appearance parameters of Led Flood Lighting**

Lamp Body Material: Aluminum Color of lamp shell: Gray

